

LIST OF FIGURES

Figure No.	Title	Page No.
1.1	Pyrochlore structure of general formula $A_2B_2O_7$ showing the 6 fold coordination of B and 8 fold coordination of A atoms.	5
1.2	Change in shape of coordination polyhedra of A and B ions with 48 f oxygen parameter X in $A_2B_2O_6O'$ Structure.	8
1.3	Variation of bond distances and bond angles as a function of 48 f Oxygen parameters.	9
1.4	The tunnel representation of pyrochlore structure projected along [111]	10
1.5	Diagrammatic representation of a projection of the ideal pyrochlore structure along [100]	10
1.6	Variation of electrostatic energy (E) Vs 48f oxygen X parameter for various oxide pyrochlores	15-16
1.7	Possible substitutions at the A and B sites of $A_2^{3+}B_2^{4+}O_7$ Oxide Pyrochlores	18
1.8	Stability field diagram for $A_2^{3+}B_2^{4+}O_7$ Pyrochlores	19
2.1	Ceramic Method	30
2.2	Principle of X-ray diffractometer and main features	39
2.3	Estwald's Sphere	40

2.4	X-ray diffraction pattern for the sample $\text{Ce}_2\text{Ti}_2\text{O}_7$	42
2.5	X-ray diffraction pattern for the sample $\text{Ce}_2\text{Sn}_2\text{O}_7$	42
2.6	X-ray diffraction pattern for the sample $\text{Y}_2\text{Ti}_2\text{O}_7$	43
2.7	X-ray diffraction pattern for the sample $\text{Y}_2\text{Sn}_2\text{O}_7$	43
2.8	X-ray diffraction pattern for the sample $\text{Sm}_2\text{Ti}_2\text{O}_7$	44
2.9	X-ray diffraction pattern for the sample $\text{Sm}_2\text{Sn}_2\text{O}_7$	44
3.1 (a)	The conductivity cell	59
3.1 (b)	Circuit diagram for electrical resistivity	59
3.2 c	Experimental setup for the measurement of DC electrical resistivity	60
3.3	Schematic diagram of experimental setup of for the measurement of thermo electric power.	61
3.4	Experimental setup for the measurement of thermoelectric power	62
3,5	Variation of $\log \rho$ Vs $1000/T$ for $\text{Ce}_2\text{Ti}_2\text{O}_7$	65
3,6	Variation of $\log \rho$ Vs $1000/T$ for $\text{Ce}_2\text{Sn}_2\text{O}_7$	66
3,7	Variation of $\log \rho$ Vs $1000/T$ for $\text{Y}_2\text{Ti}_2\text{O}_7$	67
3,8	Variation of $\log \rho$ Vs $1000/T$ for $\text{Y}_2\text{Sn}_2\text{O}_7$	68
3,9	Variation of $\log \rho$ Vs $1000/T$ for $\text{Sm}_2\text{Ti}_2\text{O}_7$	69
3,10	Variation of $\log \rho$ Vs $1000/T$ for $\text{Sm}_2\text{Sn}_2\text{O}_7$	70
3.11	Temperature variation of thermo electric power for $\text{Ce}_2\text{Sn}_2\text{O}_7$	72
3.12	Temperature variation of thermo electric power for $\text{Y}_2\text{Ti}_2\text{O}_7$	73

3.13	Temperature variation of thermo electric power for $Y_2Sn_2O_7$	74
4.1	Double layer capacitor	81
4.2	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Y_2Ti_2O_7$	84
4.3	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Ce_2Ti_2O_7$	85
4.4	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Sm_2Ti_2O_7$	86
4.5	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Y_2Sn_2O_7$	87
4.6	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Ce_2Sn_2O_7$	88
4.7	Variation of ϵ' , ϵ'' and $\tan \delta$ with $\log F$ for $Sm_2Sn_2O_7$	89
4.8	Variation of ϵ'' Vs ϵ' for $Y_2Sn_2O_7$	91
4.9	Variation of ϵ'' Vs ϵ' for $Sm_2Sn_2O_7$	92
4.10	Variation of ϵ'' Vs ϵ' for $Y_2Ti_2O_7$	93
4.11	Variation of ϵ'' Vs ϵ' for $Ce_2Sn_2O_7$	94
4.12	Variation of ϵ'' Vs ϵ' for $Sm_2Ti_2O_7$	95
4.13	Variation of ϵ'' Vs ϵ' for $Ce_2Ti_2O_7$	96
4.14	Temperature variation of dielectric constant for $Y_2Ti_2O_7$	99
4.15	Temperature variation of dielectric constant for $Ce_2Ti_2O_7$	100
4.16	Temperature variation of dielectric constant for $Sm_2Ti_2O_7$	101

4.17	Temperature variation of dielectric constant for $Y_2Sn_2O_7$	102
4.18	Temperature variation of dielectric constant for $Ce_2Sn_2O_7$	103
4.19	Temperature variation of dielectric constant for $Sm_2Sn_2O_7$.	104