

## LIST OF FIGURES

| FIGURE NO. | T I T L E   | PAGE NO.         |
|------------|---|------------------|
| 1.1        | Schematic representation of frequency dependence of the several contributions to the total polarizability.  | 8                |
| 1.2        | Schematic representation of ferroelectric hysteresis loop.  | 10               |
| 1.3(a)     | Representation of the free energy as a function of polarization for various values of $\lambda'$ for second order transition.                       | 24               |
| 1.3(b)     | Representation of spontaneous polarization and reciprocal of susceptibility near transition temperature for a second order transition.              | 24               |
| 1.4(a)     | Representation of the free energy as a function of polarization for various values of $X'$ for <del>second</del> <sup>first</sup> order transition. | <del>25</del> 27 |
| 1.4(b)     | Representation of the free energy as a function of polarization for various values of $X'$ for first order transition.                              | <del>25</del> 27 |
| 2.1        | Modified form of sawyer and tower circuit.  | 58               |
| 2.2        | Photograph of experimental set-up of dielectric hysteresis.   | 60               |
| 2.3        | Photographs of hysteresis loop at various temperatures of lead titanate ( $PbTiO_3$ ).  | 61               |
| 2.4        | Photographs of hysteresis loop at various temperatures of the solid solution system (lead, strontium) titanate.                                     | 62               |

| FIGURE NO. | T I T L E   | PAGE NO. |
|------------|---|----------|
| 2.5        | Photographs of hysteresis loop at various temperatures for the solid solution system (lead,calcium) titanate.   | 63       |
| 3.1        | Photograph of the experimental set-up for the solid state battery formation of solid solutions (lead,strontium)titanate and (lead,calcium) titanate.                            | 70       |
| 3.2        | Graphical Representation of the temperature dependence of emf for the solid solution of (lead,strontium) titanate.  | 73       |
| 3.3        | Graphical Representation of the temperature dependence of emf for the solid solution of (lead,calcium) titanate.  | 75       |
| 4.1        | Representation of the power dissipated in the crystal as a function of temperature for three different values of the applied voltage.   | 80       |
| 4.2        | Block Diagram for the experimental set-up of TANDEL.  | 86       |
| 4.3        | Photograph of the experimental set-up for the second harmonic generation and TANDEL effect.   | 88       |
| 4.4        | Graphical representation of the variation of second harmonic voltage with a d.c. bias for different a.c. voltages (volts peak) for the solid solution (lead,strontium)titanate. | 89       |
| 4.5        | Graphical representation of the variation of second harmonic voltage with a d.c. bias for different a.c. voltages (volts peak) for the solid solution (lead,calcium) titanate.  | 90       |