

## LIST OF FIGURES

<b>Fig.</b>	<b>Description</b>
1.1	Growth pattern of Indian ferrite industry
1.2	Structure of spinel ferrite
1.3 (a)	Mechanisms of polarization
1.3 (b)	Frequency dependence of polarizability
1.4	Angle between A-A, B-B and A-B cations in a spinel structure
1.5 (a)	Applications of ferrites
1.5 (b)	Relation between the characteristics of soft ferrites and their applications
2.A.1	An outline of development of manufacturing technologies of ferrite
2.A.2	Flow chart of ferrite preparation
2.A.3	Schematic representation of diffusion in ferrites
2.B.1	Schematic diagram –XRD machine
2.B.2	XRD pattern of $\text{Ni}_{0.2}\text{Cu}_{0.2}\text{Zn}_{0.6}\text{Fe}_2\text{O}_4$ sample
2.B.3	XRD pattern of $\text{Ni}_{0.3}\text{Cu}_{0.2}\text{Zn}_{0.5}\text{Fe}_2\text{O}_4$ sample
2.B.4	XRD pattern of $\text{Ni}_{0.4}\text{Cu}_{0.2}\text{Zn}_{0.4}\text{Fe}_2\text{O}_4$ sample
2.B.5	XRD pattern of $\text{Ni}_{0.5}\text{Cu}_{0.2}\text{Zn}_{0.3}\text{Fe}_2\text{O}_4$ sample
2.B.6	XRD pattern of $\text{Ni}_{0.6}\text{Cu}_{0.2}\text{Zn}_{0.2}\text{Fe}_2\text{O}_4$ sample
2.B.7	XRD pattern of $\text{Ni}_{0.7}\text{Cu}_{0.2}\text{Zn}_{0.1}\text{Fe}_2\text{O}_4$ sample
2.B.8	XRD pattern of $\text{Ni}_{0.8}\text{Cu}_{0.2}\text{Zn}_0\text{Fe}_2\text{O}_4$ sample

<b>Fig.</b>	<b>Description</b>
2.B.9	Variation of lattice parameter 'a' with content of nickel (x) for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ ferrite system
2.B.10	Variation of band lengths $R_A$ and $R_B$ with content of nickel (x) for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system
2.B.11	Variation of site radii $r_A$ and $r_B$ with content of nickel (x) for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system
3.A.1	Experimental set up for dc electrical resistivity measurements
3.A.2	Variation of $\log \rho_{dc}$ versus $1/T$ for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system for $x = 0.2$ to $0.6$
3.A.3	Variation of $\log \rho_{dc}$ versus $1/T$ for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system for $x = 0.7, 0.8$
3.A.4	Variation of $\rho_{dc}$ versus Nickel content for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system for $x = 0.2$ to $0.8$
3.B.	Experimental set up for ac conductivity measurement
3.B.1	Variation of dielectric constant with log frequency for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite system
3.B.2	Variation of dielectric loss tangent ( $\tan\delta$ ) with log frequency for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite
3.B.3	Variation of $\rho_{ac}$ versus log frequency for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}$ $\text{Fe}_2\text{O}_4$ ferrite
4.A.1	Susceptibility - Temperature curve for magnetite
4.A.2	Variation of spontaneous magnetization with temperature
4.A.3	Triangular spin configuration
4.A.4	Magnetization curve and hysteresis loop
4.A.5	Experimental set up for hysteresis loop study

<b>Fig.</b>	<b>Description</b>
4.A.6	Schematic diagram of hysteresis loop tracer
4.A.7	Hysteresis loops for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}\text{Fe}_2\text{O}_4$ ferrite ( $x = 0.2, 0.3, 0.4$ )
4.A.8	Hysteresis loops for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}\text{Fe}_2\text{O}_4$ ferrite ( $x = 0.5, 0.6, 0.7, 0.8$ )
4.A.9	Variation of saturation magnetization ( $4\pi M_s$ ) with content of nickel ( $x$ ) for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}\text{Fe}_2\text{O}_4$ samples
4.A.10	Variation of magnetic moment with content of nickel ( $x$ ) for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}\text{Fe}_2\text{O}_4$ ferrites
4.B.1	Variation of initial permeability with temperature for $\text{Ni}_x\text{Cu}_{0.2}\text{Zn}_{0.8-x}\text{Fe}_2\text{O}_4$ ferrite samples